

ADAMS KEYSWITCHES AND PUSHBUTTONS - IN STOCK



Survivor Base Pushbuttons

ADAMS pushbuttons complete with Lexan® housings, incandescent illumination and blank face. PSB bulbs not included and sold separately.

Designer™ style - plastic button head, square 1.5", height 0.125".
Survivor® style - plastic button head, diameter 1.365", height 0.125".
Survivor/Plus™ style - vandal-resistant, stainless steel #4 button head. Designed for metal panel with opening diameter 1.156" inside and 1.246" outside coined surface. Supported in panel by included spring clip.

| | | |
|----------------|----------|----------------------|
| AS458A4 | 2NO | Designer™ style |
| AS458A5 | 2NC | Survivor® style |
| AS458A6 | 1NC, 1NO | Survivor/Plus™ style |



Emergency Stop Switches

Original style survivor stop switches mount horizontal or corner-to-corner. Red plastic button, 1/8" high and 1-1/2" diameter halos.

New style switches have 1/8" high and 1-3/8" diameter halos.
Shown stop switches with Pull to Stop, Push to Run action.

| | | |
|-----------------|----------|-------------------------|
| A471A1 | 2NC, 1NO | Original Survivor Style |
| AS459A6 | 1NC, 2NO | Classic™ Style |
| AS459A2 | 2NC, 1NO | New Style Survivor |
| AS459A5 | 1NC, 2NO | New Style Survivor |
| ARW471A6 | 2NC, 1NO | Armor 10411-01 |



Survivor Base Keyswitches

All Adams keyswitches use Survivor base and are built with tough Lexan® housings. Choose from 2-, 3-, and 4-position configurations. 2-position switches are rated B300 and Q300. All locks are 5-disk tumbler type. Each switch comes with 2 keys.

Replacement keys: AE102 **Model KEY**
MM101 **Model AK-MM101**

We stock various keyswitch combinations. Please call.

| Complete keyswitch | Function | Halo designations/locations | | | | Keypulls | | | | Base contacts | Config. | Key code |
|--------------------|------------------|-----------------------------|------|----------------|-------|----------|------|------|------|---------------|----------|----------|
| | | 12:00 | 3:00 | 6:00 | 9:00 | 12:00 | 3:00 | 6:00 | 9:00 | | | |
| AS468K39 | 2000 Code | OFF | ON | | RESET | X | X | - | 0 | 4 | SP3T | WD01 |
| AS468K32 | 2000 Code | HOLD | ON | FIRE OPERATION | OFF | X | 0 | - | X | 4 | SP3T | WD01 |
| AS468K23 | Off/On | OFF | ON | | | X | X | - | - | 4 | DPDT | MM101 |
| AS469K21 | Emergency | RUN | STOP | | | X | X | - | - | 2 | DPST | AE102 |
| AS468K04 | Access | | UP | ACCESS | DOWN | X | M | - | M | 2 | 1NC, 1NO | GG101 |
| AS469K22 | Access | OFF | ON | ACCESS | | X | X | - | - | 2 | SPDT | GG101 |
| AS469K13 | Inspection | OFF | ON | INSPECTION | | X | X | - | - | 2 | SPDT | GG101 |
| AS468K24 | Inspection | OFF | ON | INSPECTION | | X | X | - | - | 4 | DPDT | GG101 |
| AS469K17 | Floor Disconnect | OFF | ON | | | X | X | - | - | 2 | SPDT | AE102 |

Note:

X = Keypull available

O = Keypull not available

- = No function

M = Momentary contact/ spring return

**QUALITY
ELEVATOR PRODUCTS, INC.**